

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 1 IDENTIFICATION OF THE SUBSTANCES / MIXTURE AND OF THE COMPANY / UNDERTAKING

PRODUCT IDENTIFIER

Product name	Red Oxide Primer
Synonyms	A1090, A1090D
Proper shipping name	AEROSOLS
Other means of identification	Not Available

RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Relevant identified uses	Application is by spray atomisation from a hand held aerosol pack Use according to manufacturer's directions.
--------------------------	--

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Registered company name	Aspec Group Pty Ltd T/A SILVERZINC.COM.AU
Address	2/10 Maiella Street Stapytton Queensland 4207 Australia
Telephone	1300 2653 425
Fax	+61 7 3287 4568
Website	www.silverzinc.com.au
Email	info@silverzinc.com.au

EMERGENCY TELEPHONE NUMBER

Association / Organisation	1300 2653 425
Emergency Telephone Numbers	0400018006
Other emergency telephone numbers	Not Available

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 2 HAZARDS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

HAZARDOUS CHEMICAL. DANGEROUS GOODS. ACCORDING TO THE WHS REGULATIONS AND THE ADG CODE.

CHEMWATCH HAZARD RATINGS

Poisons Schedule	Not Applicable
Classification ^[1]	Flammable Aerosols Category 1, Acute Toxicity (Oral) Category 4, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Skin Sensitizer Category 1, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Specific target organ toxicity - single exposure Category 3 (narcotic effects), Acute Aquatic Hazard Category 3, Chronic Aquatic Hazard Category 2
Legend	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

LABEL ELEMENTS

Hazard Pictogram(s)	
Signal Word	Danger

HAZARD STATEMENT(S)

H222	Extremely flammable aerosol.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
AUH044	Risk of explosion if heated under confinement.
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing mist/vapours/spray.

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

PRECAUTIONARY STATEMENT(S) PREVENTION

P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

PRECAUTIONARY STATEMENT(S) RESPONSE

P321	Specific treatment (see advice on this label).
P362	Take off contaminated clothing and wash before reuse.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313	IF ON SKIN: Wash with plenty of water and soap.
P333 + P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P302 + P352	IF ON SKIN: Wash with plenty of water and soap.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.

PRECAUTIONARY STATEMENT(S) STORAGE

P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.

PRECAUTIONARY STATEMENT(S) DISPOSAL

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCES

SEE SECTION BELOW FOR COMPOSITION OF MIXTURES

MIXTURES

CAS No.	% [Weight]	Name
1330-20-7	10-20	xylene
Not Available	10-20	resin, proprietary
Not Available	10-15	filler
1309-37-1	5-10	ferric oxide
64742-95-6.	2-5	naphtha petroleum, light aromatic solvent
64-17-5	1-5	ethanol
7779-90-0	1-5	zinc phosphate
115-10-6	20-40	dimethyl ether

SECTION 4 FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

Eye Contact	<p>If aerosols come in contact with the eyes:</p> <ul style="list-style-type: none"> Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If solids or aerosol mists are deposited upon the skin:</p> <ul style="list-style-type: none"> Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation.
Inhalation	<p>If aerosols, fumes or combustion products are inhaled:</p> <ul style="list-style-type: none"> Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	<ul style="list-style-type: none"> Avoid giving milk or oils. Avoid giving alcohol. If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED FOR PHOSPHATE SALTS

INTOXICATION:

Treat symptomatically.

- Always treat symptoms rather than history.
- In general, however, toxic doses exceed 20 mg/kg of ingested material (as elemental iron) with lethal doses exceeding 180 mg/kg.
- Control of iron stores depend on variation in absorption rather than excretion. Absorption occurs through aspiration, ingestion and burned skin.
- Hepatic damage may progress to failure with hypoprothrombinaemia and hypoglycaemia. Hepatorenal syndrome may occur.
- Iron intoxication may also result in decreased cardiac output and increased cardiac pooling which subsequently produces hypotension.
- Serum iron should be analysed in symptomatic patients. Serum iron levels (2-4 hrs post-ingestion) greater than 100 ug/dL indicate poisoning with levels, in excess of 350 ug/dL, being potentially serious. Emesis or lavage (for obtunded patients with no gag reflex) are the usual means of decontamination.
- Activated charcoal does not effectively bind iron.
- Catharsis (using sodium sulfate or magnesium sulfate) may only be used if the patient already has diarrhoea.
- Deferoxamine is a specific chelator of ferric (3+) iron and is currently the antidote of choice. It should be administered parenterally. [Ellenhorn and Barceloux: Medical Toxicology]

FOR LOWER ALKYL ETHERS:

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- A low-stimulus environment must be maintained.
- Monitor and treat, where necessary, for shock.
- Anticipate and treat, where necessary, for seizures.
- **DO NOT use emetics.** Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension without signs of hypovolaemia may require vasopressors.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- Ethers may produce anion gap acidosis. Hyperventilation and bicarbonate therapy might be indicated.
- Haemodialysis might be considered in patients with impaired renal function.
- Consult a toxicologist as necessary.

BRONSTEIN, A.C. AND CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE:

2ND ED. 1994

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

FOR ACUTE OR SHORT TERM REPEATED EXPOSURES TO XYLENE:

- Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- Pulmonary absorption is rapid with about 60-65% retained at rest.
- Primary threat to life from ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases ($pO_2 < 50$ mm Hg or $pCO_2 > 50$ mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
Methylhippu-ric acids in urine	1.5 gm/gm creatinine 2 mg/min	End of shift Last 4hrs of shift	

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 5 FIREFIGHTING MEASURES

EXTINGUISHING MEDIA

- **SMALL FIRE: WATER SPRAY, DRY CHEMICAL OR CO2**
- **LARGE FIRE: WATER SPRAY OR FOG.**

SPECIAL HAZARDS ARISING FROM THE SUBSTRATE OR MIXTURE

Fire Incompatibility	<ul style="list-style-type: none"> • Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

ADVICE FOR FIREFIGHTERS

Fire Fighting	<ul style="list-style-type: none"> • Alert Fire Brigade and tell them location and nature of hazard. • May be violently or explosively reactive. • Wear breathing apparatus plus protective gloves. • Prevent, by any means available, spillage from entering drains or water course. • If safe, switch off electrical equipment until vapour fire hazard removed. • Use water delivered as a fine spray to control fire and cool adjacent area. • DO NOT approach containers suspected to be hot. • Cool fire exposed containers with water spray from a protected location. • If safe to do so, remove containers from path of fire. • Equipment should be thoroughly decontaminated after use.
Fire Explosion/Hazard	<ul style="list-style-type: none"> • Liquid and vapour are highly flammable. • Severe fire hazard when exposed to heat or flame. • Vapour forms an explosive mixture with air. • Severe explosion hazard, in the form of vapour, when exposed to flame or spark. • Vapour may travel a considerable distance to source of ignition. • Heating may cause expansion or decomposition with violent container rupture. • Aerosol cans may explode on exposure to naked flames. • Rupturing containers may rocket and scatter burning materials. • Hazards may not be restricted to pressure effects. • May emit acrid, poisonous or corrosive fumes. • On combustion, may emit toxic fumes of carbon monoxide (CO). <p>Combustion products include:</p> <ul style="list-style-type: none"> • carbon dioxide (CO2) • other pyrolysis products typical of burning organic material. • Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.
HAZCHEM	Not Applicable

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES - **SEE SECTION 8**

ENVIRONMENTAL PRECAUTIONS - **SEE SECTION 12**

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Minor Spills	<ul style="list-style-type: none"> • Clean up all spills immediately. • Avoid breathing vapours and contact with skin and eyes. • Wear protective clothing, impervious gloves and safety glasses. • Shut off all possible sources of ignition and increase ventilation. • Wipe up. • If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. • Undamaged cans should be gathered and stowed safely.
Major Spills	<ul style="list-style-type: none"> • Clear area of personnel and move upwind. • Alert Fire Brigade and tell them location and nature of hazard. • May be violently or explosively reactive. • Wear breathing apparatus plus protective gloves. • Prevent, by any means available, spillage from entering drains or water courses • No smoking, naked lights or ignition sources. • Increase ventilation. • Stop leak if safe to do so. • Water spray or fog may be used to disperse / absorb vapour. • Absorb or cover spill with sand, earth, inert materials or vermiculite. • If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. • Undamaged cans should be gathered and stowed safely. • Collect residues and seal in labelled drums for disposal.

PERSONAL PROTECTIVE EQUIPMENT ADVICE IS CONTAINED IN SECTION 8 OF THE SDS.

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 7 HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Safe handling

- **DO NOT allow clothing wet with material to stay in contact with skin**
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- **DO NOT enter confined spaces until atmosphere has been checked.**
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- **When handling, DO NOT eat, drink or smoke.**
- **DO NOT incinerate or puncture aerosol cans.**
- **DO NOT spray directly on humans, exposed food or food utensils.**
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within this SDS.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

Other Information

- Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can
- Store in original containers in approved flammable liquid storage area.
- **DO NOT store in pits, depressions, basements or areas where vapours may be trapped.**
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed. Contents under pressure.
- Store away from incompatible materials.
- Store in a cool, dry, well ventilated area.
- Avoid storage at temperatures higher than 40 deg C.
- Store in an upright position.
- Protect containers against physical damage.
- Check regularly for spills and leaks.
- Observe manufacturer's storage and handling recommendations contained within this SDS.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Suitable container

- Aerosol dispenser.
- Check that containers are clearly labelled.

Storage Incompatibility

- Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates.



LEGEND

- X – MUST NOT BE STORED TOGETHER
O – MAY BE STORED TOGETHER WITH SPECIFIC PREVENTIONS
+ – MAY BE STORED TOGETHER

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

CONTROL PARAMETERS - OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Sampling Time	TWA	STEL	Peak	Notes
Australia Exposure Standards	xylene	Xylene (o-, m-, p- isomers)	80ppm / 350mg / m3	655mg /m3 / 150ppm	Not Available	Not Available
Australia Exposure Standards	ferric oxide	Iron oxide fume (Fe2O3) (as Fe)	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	ethanol	Ethyl alcohol	1000 ppm / 1880 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	dimethyl ether	Dimethyl ether	400ppm / 760mg / m3	950mg / m3 / 500ppm	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material Name	TEEL-1	TEEL-2	TEEL-3
xylene	Xylenes	Not Available	Not Available	Not Available
ferric oxide	Iron oxide; (Ferric oxide)	15 mg/m3	360 mg/m3	2,200 mg/m3
naphtha petroleum, light aromatic solvent	Naphtha (coal tar); includes solvent naphtha, petroleum (64742-88-7), naphtha (petroleum) light aliphatic, rubber solvent (64742-89-8), heaevy catalytic cracked (64741-54-4), light straight run (64741-46-4), heavy aliphatic solvent (64742-96-7), high flash aromatic and aromatic solvent naphtha (64742-95-6)	1,200 mg/m3	6,700 mg/m3	40,000 mg/m3
ethanol	Ethanol: (Ethyl alcohol)	Not Available	Not Available	15000* ppm
zinc phosphate	Zinc phosphate (3:2)	12mg / m3	36mg / m3	220mg / m3
dimethyl ether	Methyl ether; (Dimethyl ether)	3000ppm	3800*ppm	7200*ppm

Ingredient	Original IDLH	Revised IDLH
xylene	900ppm	Not Available
ferric oxide	2,500 mg/m3	Not Available
naphtha petroleum, light aromatic solvent	Not Available	Not Available
ethanol	3,300 ppm	Not Available
zinc phosphate	Not Available	Not Available
dimethyl ether	Not Available	Not Available

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

EXPOSURE CONTROLS

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

- Process controls which involve changing the way a job activity or process is done to reduce the risk.
- Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
- Employers may need to use multiple types of controls to prevent employee overexposure.
- General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection.
- Provide adequate ventilation in warehouse or closed storage areas.
- Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Appropriate engineering controls


Type of Contaminant	Speed
aerosols, (released at low velocity into zone of active generation)	0.5-1m/s
direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)	1-2.5m/s (200-500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Personal protection



Eye and face protection

- Safety glasses with side shields.
- Chemical goggles
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 ornational equivalent]

Skin protection

See Hand protection below

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

Hands/feet protection	No special equipment needed when handling small quantities. OTHERWISE: <ul style="list-style-type: none"> For potentially moderate exposures: <ul style="list-style-type: none"> Wear general protective gloves, eg. light weight rubber gloves. For potentially heavy exposures: <ul style="list-style-type: none"> Wear chemical protective gloves, eg. PVC. and safety footwear.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: <ul style="list-style-type: none"> Overalls. Skin cleansing cream. Eyewash unit. Do not spray on hot surfaces. The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton. Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost. BREThERICK: Handbook of Reactive Chemical Hazards.

RECOMMENDED MATERIAL(S)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index". The effect(s) of the following substance(s) are taken into account in the *computer generated* selection:
Grey Etch Primer

Material	CPI
BUTYL	C
BUTYL/NEOPRENE	C
HYPALON	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PE	C
PE/EVAL/PE	C
PVA	C
PVC	C
PVDC/PE/PVDC	C
SARANEX-23	C
TEFLON	C
VITON	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term

immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation.

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

RESPIRATORY PROTECTION

Type BAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS	-	AX-PAPR-AUS / Class 1
up to 50 x ES	-	AX-AUS / Class 1	-
up to 100 x ES	-	AX-2	AX-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours

B AUS or B1 = Acid gasses

B2 = Acid gas or hydrogen cyanide(HCN)

B3 = Acid gas or hydrogen cyanide(HCN)

E = Sulfur dioxide(SO2)

G = Agricultural chemicals

K = Ammonia(NH3)

Hg = Mercury

NO = Oxides of nitrogen

MB = Methyl bromide

AX = Low boiling point organic compounds(below 65 degC)

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used.

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Red coloured flammable aerosol; not miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point/freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point & boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	-81 (propellant)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	>50
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> • Elevated temperatures. • Presence of open flame. • Product is considered stable. • Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 1.1 TOXICOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

Inhaled

- Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.
- Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.
- There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Heart stoppage may result from cardiovascular collapse. A slow heart rate and low blood pressure may also occur.
- Alkylbenzenes are not generally toxic except at high levels of exposure. Their breakdown products have low toxicity and are easily eliminated from the body.
- Animal testing shows that the most common signs of inhalation overdose is inco-ordination and drowsiness.
- Inhalation of toxic gases may cause:
Central Nervous System effects including depression, headache, confusion, dizziness, stupor, coma and seizures;
respiratory: acute lung swellings, shortness of breath, wheezing, rapid breathing, other symptoms and respiratory arrest;
heart: collapse, irregular heartbeats and cardiac arrest;
gastrointestinal: irritation, ulcers, nausea and vomiting (may be bloody), and abdominal pain.
- Following inhalation, ethers cause lethargy and stupor. Inhaling lower alkyl ethers results in headache, dizziness, weakness, blurred vision, seizures and possible coma.
- Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure.
- Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.
- **WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.**
- Headache, fatigue, tiredness, irritability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers.
- Xylene is a central nervous system depressant
- Inhalational exposure to diethyl ether may cause immediate unconsciousness, inco-ordination, blurring of vision, headache, dizziness and death depending on dose and extent of exposure. It is a weak heart sensitiser in dogs.

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

- Accidental ingestion of the material may be damaging to the health of the individual.
- Ingestion of ethanol (ethyl alcohol, "alcohol") may produce nausea, vomiting, bleeding from the digestive tract, abdominal pain, and diarrhoea.
- Effects on the body:

Blood Concentration

Effects

Ingestion

<1.5 G/L	Mild: impaired vision, co-ordination and reaction time; emotional instability
1.5-3.0 G/L	Moderate: Slurred speech, confusion, inco-ordination, emotional instability, disturbances in perception and senses, possible blackouts, and impaired objective performance in standardized tests. Possible double vision, flushing, fast heart rate, sweating and incontinence. Slow breathing may occur rarely and fast breathing may develop in cases of metabolic acidosis, low blood sugar and low blood potassium. Central nervous system depression may progress to coma.
3-5 G/L	Severe: cold clammy skin, low body temperature and low blood pressure. Atrial fibrillation and heart block have been reported. Depression of breathing may occur, respiratory failure may follow serious poisoning, choking on vomit may result in lung inflammation and swelling. Convulsions due to severe low blood sugar may also occur. Acute liver inflammation may develop.

- Not normally a hazard due to physical form of product.
- Considered an unlikely route of entry in commercial/industrial environments
- Ingestion of alkyl ethers may produce stupor, blurred vision, headache, dizziness and irritation of the nose and throat. Respiratory distress and asphyxia may result.

Skin Contact

- Skin contact with the material may be harmful; systemic effects may result following absorption.
- This material can cause inflammation of the skin on contact in some persons.
- Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.
- Spray mist may produce discomfort
- Alkyl ethers may defat and dehydrate the skin producing dermatoses. Absorption may produce headache, dizziness, and central nervous system depression.
- Open cuts, abraded or irritated skin should not be exposed to this material

Eye

- This material can cause eye irritation and damage in some persons.
- Direct contact of the eye with ethanol (alcohol) may cause an immediate stinging and burning sensation, with reflex closure of the lid, and a temporary, tearing injury to the cornea together with redness of the conjunctiva. Discomfort may last 2 days but usually the injury heals without treatment.
- Not considered to be a risk because of the extreme volatility of the gas. Eye contact with alkyl ethers (vapour or liquid) may produce irritation, redness and tears.

Chronic

- Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.
- There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby
- Prolonged exposure to ethanol may cause damage to the liver and cause scarring. It may also worsen damage caused by other agents.
- Main route of exposure to the gas in the workplace is by inhalation.
- Chronic exposure to alkyl ethers may result in loss of appetite, excessive thirst, fatigue, and weight loss.
- Chronic excessive intake of iron have been associated with damage to the liver and pancreas. People with a genetic disposition to poor control over iron are at an increased risk.
- There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.
- Women exposed to xylene in the first 3 months of pregnancy showed a slightly increased risk of miscarriage and birth defects. Evaluation of workers chronically exposed to xylene has demonstrated lack of genetic toxicity.
- Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).
- Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS]

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

RED OXIDE PRIMER	TOXICITY		IRRITATION	
	Not Available		Not Available	
XYLENE	TOXICITY		IRRITATION	
	Dermal (rabbit) LD50: >1700 mg/kg ^[2]		Eye (human): 200ppm - irritant	
	Inhalation (rat) LC50: 4994.295 mg/l/4h ^[2]		Eye (rabbit): 5mg / 24h - SEVERE	
	Oral (rat) LD50: 3523-8700 mg/kg ^[2]		Eye (rabbit): 87mg - mild	
			Eye: adverse effect observed (irritating) ^[1]	
			Skin (rabbit):500mg / 24h - moderate	
FERRIC OXIDE	TOXICITY		IRRITATION	
	Oral (rat) LD50: >10000 mg/kg ^[2]		Not Available	
NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT	TOXICITY		IRRITATION	
	Dermal (rabbit) LD50: > 1900 mg /kg ^[2]		Eye: no adverse effect observed (not irritating) ^[1]	
	Inhalation (rat) LC50: 7331.62506 mg /l/8h ^[2]		Skin: adverse effect observed (irritating) ^[1]	
	Oral (rat) LD50: = 4500 mg / kg ^[1]			
ETHANOL	TOXICITY		IRRITATION	
	Inhalation (rat) LC50: 124.7 mg/l/4h ^[2]		Eye (rabbit): 500mg SEVERE	
	Oral (rat) LD50: =1501 mg / kg ^[2]		Eye (rabbit): 100 mg/24h - moderate	
			Eye: adverse effect observed (irritating) ^[1]	
			Skin (rabbit): 20 mg/24h - moderate	
			Skin (rabbit): 400 mg (open)-mild	
ZINC PHOSPHATE	TOXICITY		IRRITATION	
	Oral (rat) LD50: >5000mg / kg ^[2]		Eye: no adverse effect observed (not irritating) ^[1]	
DIMETHYL ETHER	TOXICITY		IRRITATION	
	Inhalation (rat) LC50: 308mg / l ^[2]		Not Available	

LEGEND

1. VALUE OBTAINED FROM EUROPE ECHA REGISTERED SUBSTANCES - ACUTE TOXICITY

2.* VALUE OBTAINED FROM MANUFACTURER'S SDS. UNLESS OTHERWISE SPECIFIED DATA EXTRACTED FROM RTECS - REGISTER OF TOXIC EFFECT OF CHEMICAL SUBSTANCES

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

XYLENE	<ul style="list-style-type: none"> • Reproductive effector in rats • The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. • The substance is classified by IARC as Group 3: • NOT classifiable as to its carcinogenicity to humans. • Evidence of carcinogenicity may be inadequate or limited in animal testing.
FERRIC OXIDE	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.</p>
NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT	<p>Inhalation (rat) TCLo: 1320 ppm/6h/90D-I * [Devoe] For Low Boiling Point Naphthas (LBPNS): Acute toxicity: LBPNS generally have low acute toxicity by the oral (median lethal dose [LD50] in rats > 2000 mg/kg-bw), inhalation (LD50 in rats > 5000 mg/m3 and dermal (LD50 in rabbits > 2000 mg/kg-bw) routes of exposure. Most LBPNS are mild to moderate eye and skin irritants in rabbits, with the exception of heavy catalytic cracked and heavy catalytic reformed naphthas, which have higher primary skin irritation indices.</p> <p>Sensitisation: LBPNS do not appear to be skin sensitizers, but a poor response in the positive control was also noted in these studies</p> <p>Repeat dose toxicity: The lowest-observed-adverse-effect concentration (LOAEC) and lowest-observed-adverse-effect level (LOAEL) values identified following short-term (2-89 days) and subchronic (greater than 90 days) exposure to the LBPNS substances. These values were determined for a variety of endpoints after considering the toxicity data for all LBPNS in the group. Most of the studies were carried out by the inhalation route of exposure. Renal effects, including increased kidney weight, renal lesions (renal tubule dilation, necrosis) and hyaline droplet formation, observed in male rats exposed orally or by inhalation to most LBPNS, were considered species- and sex-specific. These effects were determined to be due to a mechanism of action not relevant to humans -specifically, the interaction between hydrocarbon metabolites and alpha-2-microglobulin, an enzyme not produced in substantial amounts in female rats, mice and other species, including humans. The resulting nephrotoxicity and subsequent carcinogenesis in male rats were therefore not considered in deriving LOAEC/LOAEL values.</p> <p>Only a limited number of studies of short-term and subchronic duration were identified for site-restricted LBPNS. The lowest LOAEC identified in these studies, via the inhalation route, is 5475 mg/m3, based on a concentration-related increase in liver weight in both male and female rats following a 13-week exposure to light catalytic cracked naphtha. Shorter exposures of rats to this test substance resulted in nasal irritation at 9041 mg/m3</p> <p>No systemic toxicity was reported following dermal exposure to light catalytic cracked naphtha, but skin irritation and accompanying histopathological changes were increased, in a dose-dependent manner, at doses as low as 30 mg/kg-bw per day when applied 5 days per week for 90 days in rats.</p> <p>No non-cancer chronic toxicity studies (= 1 year) were identified for site-restricted LBPNS and very few non-cancer chronic toxicity studies were identified for other LBPNS. An LOAEC of 200 mg/m3 was noted in a chronic inhalation study that exposed mice and rats to unleaded gasoline (containing 2% benzene). This inhalation LOAEC was based on ocular discharge and ocular irritation in rats. At the higher concentration of 6170 mg/m3, increased kidney weight was observed in male and female rats (increased kidney weight was also observed in males only at 870 mg/m3). Furthermore, decreased body weight in male and female mice was also observed at 6170 mg/m3</p> <p>A LOAEL of 714 mg/kg-bw was identified for dermal exposure based on local skin effects (inflammatory and degenerative skin changes) in mice following application of naphtha for 105 weeks. No systemic toxicity was reported.</p> <p>Genotoxicity: Although few genotoxicity studies were identified for the site-restricted LBPNS, the genotoxicity of several other LBPNS substances has been evaluated using a variety of in vivo and in vitro assays. While in vivo genotoxicity assays were negative overall, the in vitro tests exhibited mixed results. For in vivo genotoxicity tests, LBPNS exhibited negative results for chromosomal aberrations and micronuclei induction, but exhibited positive results in one sister chromatid exchange assay although this result was not considered definitive for clastogenic activity as no genetic material was unbalanced or lost. Mixtures that were tested, which included a number of light naphthas, displayed mixed results (i.e., both positive and negative for the same assay) for chromosomal aberrations and negative results for the dominant lethal mutation assay.</p>

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

Unleaded gasoline (containing 2% benzene) was tested for its ability to induce unscheduled deoxyribonucleic acid (DNA) synthesis (UDS) and replicative DNA synthesis (RDS) in rodent hepatocytes and kidney cells. UDS and RDS were induced in mouse hepatocytes via oral exposure and RDS was induced in rat kidney cells via oral and inhalation exposure. Unleaded gasoline (benzene content not stated) exhibited negative results for chromosomal aberrations and the dominant lethal mutation assay and mixed results for atypical cell foci in rodent renal and hepatic cells.

For in vitro genotoxicity studies, LBPNS were negative for six out of seven Ames tests, and were also negative for UDS and for forward mutations LBPNS exhibited mixed or equivocal results for the mouse lymphoma and sister chromatid exchange assays, as well as for cell transformation and positive results for one bacterial DNA repair assay. Mixtures that were tested, which included a number of light naphthas, displayed negative results for the Ames and mouse lymphoma assays Gasoline exhibited negative results for the Ames test battery, the sister chromatid exchange assay and for one mutagenicity assay. Mixed results were observed for UDS and the mouse lymphoma assay.

While the majority of in vivo genotoxicity results for LBPNS substances are negative, the potential for genotoxicity of LBPNS as a group cannot be discounted based on the mixed in vitro genotoxicity results.

Carcinogenicity:
Although a number of epidemiological studies have reported increases in the incidence of a variety of cancers, the majority of these studies are considered to contain incomplete or inadequate information. Limited data, however, are available for skin cancer and leukemia incidence, as well as mortality among petroleum refinery workers. It was concluded that there is limited evidence supporting the view that working in petroleum refineries entails a carcinogenic risk (Group 2A carcinogen). IARC (1989a) also classified gasoline as a Group 2B carcinogen; it considered the evidence for carcinogenicity in humans from gasoline to be inadequate and noted that published epidemiological studies had several limitations, including a lack of exposure data and the fact that it was not possible to separate the effects of combustion products from those of gasoline itself.

Similar conclusions were drawn from other reviews of epidemiological studies for gasoline (US EPA 1987a, 1987b). Thus, the evidence gathered from these epidemiological studies is considered to be inadequate to conclude on the effects of human exposure to LBPNS substances.

No inhalation studies assessing the carcinogenicity of the site-restricted LBPNS were identified. Only unleaded gasoline has been examined for its carcinogenic potential, in several inhalation studies. In one study, rats and mice were exposed to 0, 200, 870 or 6170 mg/m³ of a 2% benzene formulation of the test substance, via inhalation, for approximately 2 years. A statistically significant increase in hepatocellular adenomas and carcinomas, as well as a non-statistical increase in renal tumours, were observed at the highest dose in female mice. A dose-dependent increase in the incidence of primary renal neoplasms was also detected in male rats, but this was not considered to be relevant to humans, as discussed previously. Carcinogenicity was also assessed for unleaded gasoline, via inhalation, as part of initiation/promotion studies. In these studies, unleaded gasoline did not appear to initiate tumour formation, but did show renal cell and hepatic tumour promotion ability, when rats and mice were exposed, via inhalation, for durations ranging from 13 weeks to approximately 1 year using an initiation/promotion protocol. However, further examination of data relevant to the composition of unleaded gasoline demonstrated that this is a highly-regulated substance; it is expected to contain a lower percentage of benzene and has a discrete component profile when compared to other substances in the LBPNS group.

Both the European Commission and the International Agency for Research on Cancer (IARC) have classified LBPNS substances as carcinogenic.

All of these substances were classified by the European Commission (2008) as Category 2 (R45: may cause cancer) (benzene content = 0.1% by weight). IARC has classified gasoline, an LBPNS, as a Group 2B carcinogen (possibly carcinogenic to humans) and "occupational exposures in petroleum refining" as Group 2A carcinogens (probably carcinogenic to humans).

Several studies were conducted on experimental animals to investigate the dermal carcinogenicity of LBPNS. The majority of these studies were conducted through exposure of mice to doses ranging from 694-1351 mg/kg-bw, for durations ranging from 1 year to the animals' lifetime or until a tumour persisted for 2 weeks. Given the route of exposure, the studies specifically examined the formation of skin tumours. Results for carcinogenicity via dermal exposure are mixed. Both malignant and benign skin tumours were induced with heavy catalytic cracked naphtha, light catalytic cracked naphtha, light straight-run naphtha and naphtha. Significant increases in squamous cell carcinomas were also observed when mice were dermally treated with Stoddard solvent, but the latter was administered as a mixture (90% test substance), and the details of the study were not available. In contrast, insignificant increases in tumour formation or no tumours were observed when light alkylate naphtha, heavy catalytic reformed naphtha, sweetened naphtha, light catalytically cracked naphtha

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

Reproductive/ Developmental toxicity:

No reproductive or developmental toxicity was observed for the majority of LBP substances evaluated. Most of these studies were carried out by inhalation exposure in rodents.

NOAEC values for reproductive toxicity following inhalation exposure ranged from 1701 mg/m³ (CAS RN 8052-41-3) to 27 687 mg/m³ (CAS RN 64741-63-5) for the LBP substances group evaluated, and from 7690 mg/m³ to 27 059 mg/m³ for the site-restricted light catalytic cracked and full-range catalytic reformed naphthas. However, a decreased number of pups per litter and higher frequency of post-implantation loss were observed following inhalation exposure of female rats to hydrotreated heavy naphtha (CAS RN 64742-48-9) at a concentration of 4679 mg/m³, 6 hours per day, from gestational days 7-20. For dermal exposures, NOAEL values of 714 mg/kg-bw (CAS RN 8030-30-6) and 1000 mg/kg-bw per day (CAS RN 68513-02-0) were noted. For oral exposures, no adverse effects on reproductive parameters were reported when rats were given site-restricted light catalytic cracked naphtha at 2000 mg/kg on gestational day 13.

For most LBPs, no treatment-related developmental effects were observed by the different routes of exposure. However, developmental toxicity was observed for a few naphthas. Decreased foetal body weight and an increased incidence of ossification variations were observed when rat dams were exposed to light aromatized solvent naphtha, by gavage, at 1250 mg/kg-bw per day. In addition, pregnant rats exposed by inhalation to hydrotreated heavy naphtha at 4679 mg/m³ delivered pups with higher birth weights. Cognitive and memory impairments were also observed in the offspring.

Low Boiling Point Naphthas [Site-Restricted]

Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins.

The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the hydrophobic hydrocarbons are ingested in association with fats in the diet. Some hydrocarbons may appear unchanged as in the lipoprotein particles in the gut lymph, but most hydrocarbons partly separate from fats and undergo metabolism in the gut cell. The gut cell may play a major role in determining the proportion of hydrocarbon that becomes available to be deposited unchanged in peripheral tissues such as in the body fat stores or the liver.

For trimethylbenzenes:

Absorption of 1,2,4-trimethylbenzene occurs after exposure by swallowing, inhalation, or skin contact. In the workplace, inhalation and skin contact are the most important routes of absorption; whole-body toxic effects from skin absorption are unlikely to occur as the skin irritation caused by the chemical generally leads to quick removal. The substance is fat-soluble and may accumulate in fatty tissues. It is also bound to red blood cells in the bloodstream. It is excreted from the body both by exhalation and in the urine.

Acute toxicity: Direct contact with liquid 1,2,4-trimethylbenzene is irritating to the skin, and breathing the vapour is irritating to the airway, causing lung inflammation. Breathing high concentrations of the chemical vapour causes headache, fatigue and drowsiness. In humans, liquid 1,2,4-trimethylbenzene is irritating to the skin and inhalation of the vapour causes chemical pneumonitis. Direct skin contact causes dilation of blood vessels, redness and irritation.

Nervous system toxicity: 1,2,4-trimethylbenzene depresses the central nervous system. Exposure to solvent mixtures in the workplace containing the chemical causes headache, fatigue, nervousness and drowsiness.

Subacute/chronic toxicity: Long-term exposure to solvents containing 1,2,4-trimethylbenzene may cause nervousness, tension and inflammation of the bronchi. Painters that worked for several years with a solvent containing 50% 1,2,4-trimethylbenzene and 30% 1,3,5-trimethylbenzene showed nervousness, tension and anxiety, asthmatic bronchitis, anaemia and changes in blood clotting; blood effects may have been due to trace amounts of benzene. Animal testing showed that inhaling trimethylbenzene may alter blood counts, with reduction in lymphocytes and an increase in neutrophils.

Genetic toxicity: Animal testing does not show that the C9 fraction causes mutations or chromosomal aberrations.

Developmental / reproductive toxicity: Animal testing showed that the C9 fraction of 1,2,4-trimethylbenzene caused reproductive toxicity.

For C9 aromatics (typically trimethylbenzenes – TMBs)

Acute toxicity: Animal testing shows that semi-lethal concentrations and doses vary amongst this group. The semilethal concentrations for inhalation range from 6000 to 10000 mg/cubic metre for C9 aromatic naphtha and 18000-24000 mg/cubic metre for 1,2,4- and 1,3,5-TMB, respectively.

Irritation and sensitization: Results from animal testing indicate that C9 aromatic hydrocarbon solvents are mildly to moderately irritating to the skin, minimally irritating to the eye, and have the potential to irritate the airway and cause depression of breathing rate. There is no evidence that it sensitizes skin.

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

Repeated dose toxicity: Animal studies show that chronic inhalation toxicity for C9 aromatic hydrocarbon solvents is slight. Similarly, oral exposure does not appear to pose a high toxicity hazard for pure trimethylbenzene isomers.

Mutation-causing ability: No evidence of mutation-causing ability and genetic toxicity was found in animal and laboratory testing. Reproductive and developmental toxicity: No definitive effects on reproduction were seen, although reduction in weight in developing animals may be seen at concentrations that are toxic to the mother.

For petroleum: This product contains benzene, which can cause acute myeloid leukaemia, and n-hexane, which can be metabolized to compounds which are toxic to the nervous system. This product contains toluene, and animal studies suggest high concentrations of toluene lead to hearing loss. This product contains ethyl benzene and naphthalene, from which animal testing shows evidence of tumour formation.

Cancer-causing potential: Animal testing shows inhaling petroleum causes tumours of the liver and kidney; these are however not considered to be relevant in humans.

Mutation-causing potential: Most studies involving gasoline have returned negative results regarding the potential to cause mutations, including all recent studies in living human subjects (such as in petrol service station attendants).

Reproductive toxicity: Animal studies show that high concentrations of toluene (>0.1%) can cause developmental effects such as lower birth weight and developmental toxicity to the nervous system of the foetus. Other studies show no adverse effects on the foetus.

Human effects: Prolonged or repeated contact may cause defatting of the skin which can lead to skin inflammation and may make the skin more susceptible to irritation and penetration by other materials. Animal testing shows that exposure to gasoline over a lifetime can cause kidney cancer, but the relevance in humans is questionable.

XYLENE & ETHANOL

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Acute Toxicity	✓	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

LEGEND



✗ - DATA EITHER NOT AVAILABLE OR DOES NOT FILL THE CRITERIA FOR CLASSIFICATION

✓ - DATA AVAILABLE TO MAKE CLASSIFICATION

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 12 ECOLOGICAL INFORMATION | TOXICITY

RED OXIDE PRIMER

Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

XYLENE

Endpoint	Test Duration (hr)	Species	Value	Source
LC50	96	Fish	2.6mg/L	2
EC50	48	Crustacea	1.8mg/L	2
EC50	72	Algae or other aquatic plants	3.2mg/L	2
NOEC	73	Algae or other aquatic plants	0.44mg/L	2

FERRIC OXIDE

Endpoint	Test Duration (hr)	Species	Value	Source
LC50	96	Fish	0.05mg/L	2
EC50	48	Crustacea	5.11mg/L	2
EC50	72	Algae or other aquatic plants	18mg/L	2
NOEC	504	Crustacea	0.52mg/L	2

NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT

Endpoint	Test Duration (hr)	Species	Value	Source
LC50	96	Fish	4.1mg/L	2
EC50	48	Crustacea	3.2mg/L	2
EC50	72	Algae or other aquatic plants	>1-mg/L	2
NOEC	72	Fish	=1mg/L	1

ETHANOL

Endpoint	Test Duration (hr)	Species	Value	Source
LC50	96	Fish	11-mg/L	2
EC50	48	Crustacea	2mg/L	4
EC50	96	Algae or other aquatic plant	17.921mg/L	4
NOEC	2016	Fish	0.000375mg/L	4

ZINC PHOSPHATE

Endpoint	Test Duration (hr)	Species	Value	Source
LC50	96	Fish	0.001-0.58mg/L	2
EC50	48	Crustacea	0.001-0.833mg/L	2
NOEC	72	Algae or other aquatic plants	0.00038608mg/L	2

DIMETHYL ETHER

Endpoint	Test Duration (hr)	Species	Value	Source
LC50	96	Fish	1-783.04mg/L	2
EC50	48	Crustacea	>4400.0mg/L	2
EC50	96	Algae or other aquatic plants	154.917mg/L	2
NOEC	48	Crustacea	>4000mg/L	1

LEGEND

EXTRACTED FROM 1. IUCLID TOXICITY DATA | 2. EUROPE ECHA REGISTERED SUBSTANCES - ECOTOXICOLOGICAL INFORMATION - AQUATIC TOXICITY | 3. EPIWIN SUITE | 3.12 (QSAR) - AQUATIC TOXICITY DATA (ESTIMATED) | 4. US EPA, ECOTOX DATABASE - AQUATIC TOXICITY DATA | 5. ECETOC AQUATIC HAZARD ASSESSMENT DATA | 6. NITE (JAPAN) - BIOCONCENTRATION DATA | 7. METI (JAPAN) - BIOCONCENTRATION DATA | 8. VENDOR DATA

TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT.

DO NOT DISCHARGE INTO SEWER OR WATERWAYS.

SILVER ZINC SUPPLIES | ABN: 58 997 237 445 | (07) 3287 4567

silverzinc.com.au | orders@silverzinc.com.au UNIT 2/10 MAIELLA ST, STAPYLTON, QLD 4207

SILVER
ZINC
SUPPLIES

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.
- Wastes resulting from use of the product must be disposed of on site or at approved waste sites.
- For Aromatic Substances Series:
- Environmental Fate: Large, molecularly complex polycyclic aromatic hydrocarbons, or PAHs, are persistent in the environment longer than smaller PAHs.
- Atmospheric Fate: PAHs are 'semi-volatile substances' which can move between the atmosphere and the Earth's surface in repeated, temperature-driven cycles of deposition and volatilization. Terrestrial Fate: BTEX compounds have the potential to move through soil and contaminate ground water, and their vapors are highly flammable and explosive.
- Ecotoxicity - Within an aromatic series, acute toxicity increases with increasing alkyl substitution on the aromatic nucleus. The order of most toxic to least in a study using grass shrimp and brown shrimp was dimethylnaphthalenes > methylnaphthalenes > naphthalenes. Anthracene is a phototoxic PAH. UV light greatly increases the toxicity of anthracene to bluegill sunfish. Biological resources in strong sunlight are at more risk than those that are not. PAHs in general are more frequently associated with chronic risks.
- For Ethanol:
- log Kow: -0.31 to -0.32;
- Koc 1: Estimated BCF= 3;
- Half-life (hr) air: 144;
- Half-life (hr) H₂O surface water: 144;
- Henry's atm m³ /mol: 6.29E-06;
- BOD 5 if unstated: 0.93-1.67,63%
- COD: 1.99-2.11,97%;
- ThOD : 2.1.
- Environmental Fate: Terrestrial - Ethanol quickly biodegrades in soil but may leach into ground water; most is lost by evaporation. Ethanol is expected to have very high mobility in soil. Volatilization of ethanol from moist soil surfaces is expected to be an important fate process. The potential for volatilization of ethanol from dry soil surfaces may exist.
- Biodegradation is expected to be an important fate process for ethanol based on half-lives on the order of a few days for ethanol in sandy soil/groundwater microcosms.
- Atmospheric Fate: Ethanol is expected to exist solely as a vapour in the ambient atmosphere. Vapour-phase ethanol is degraded in the atmosphere by reaction with photochemically produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 5 days. Ethanol readily degraded by reaction with photochemically produced hydroxy radicals; release into air will result in photodegradation and wet deposition.
- Aquatic Fate: When released into water ethanol readily evaporates and is biodegradable. Ethanol is not expected to adsorb to suspended solids and sediment. Volatilization from water surfaces is expected and volatilization half-lives for a model river and model lake are 3 and 39 days, respectively. Bioconcentration in aquatic organisms is considered to be low.
- Hydrolysis and photolysis in sunlit surface waters is not expected to be an important environmental fate process for ethanol and is unlikely to be persistent in aquatic environments.
- For C9 aromatics (typically trimethylbenzene - TMBs)
- Chemicals in this category possess properties indicating a hazard for the environment (acute toxicity for fish, invertebrates, and algae from 1 to 10 mg/L). Category members are readily biodegradable, except 1,3,5-trimethylbenzene (CAS RN 108-67-8). Category members are not expected to be bioaccumulative.
- Environmental Fate:
- In the air, category member constituents have the potential to rapidly degrade through indirect photolytic processes mediated primarily by hydroxyl radicals with calculated degradation half-lives ranging from 0.54 to 2.81 days (based on a 12-hour day and a hydroxyl radical concentration of 5x10⁵). Aqueous photolysis and hydrolysis will not contribute to the transformation of category chemical constituents in aquatic environments because they are either poorly reactive or not susceptible to these reactions.
- Results of the Mackay Level I environmental distribution model show that chemical constituents of C9 Aromatic Hydrocarbon Solvents Category members have the potential to partition to air (96.8 to 98.9 %), with a negligible amount partitioning to water (0.2 to 0.6%) and soil (0.9 to 2.7%). In comparison, Level III modeling indicates that category members partition primarily to soil (66.3 to 79.6%) and water (17.8 to 25.0%) compartments rather than air (2.4 to 8.4%) when an equal emission rate (1000 kg/hr) is assumed to each of the air, water, and soil compartments. When release (1000 kg/hr) is modeled only to either the air, water, or soil compartment, constituents are indicated in the modeling to partition primarily (>94%) to the compartment to which they are emitted as advection and degradation influence constituent concentration in compartments to which constituents are not released.
- Solvent naphtha, (pet.), light aromatic (CAS RN 64742-95-6), 1,2,4-trimethylbenzene (CAS RN 95-63-6), and 1-ethyl-3-methylbenzene (CAS RN 620-14-4) were determined to be readily biodegradable based on the studies that used the TG OECD 301F (the latter substance is used to characterize the potential biodegradability of the category member, ethylmethylbenzene (CAS RN 25550-14-5)). These three substances exceed 60% biodegradation in 28 days and met the 10-day window criterion for ready biodegradation. In comparison 1,3,5-trimethylbenzene (CAS RN 108-67-8) was not readily biodegradable. It achieved 42% biodegradation after 28 days and 60% biodegradation after 39 days. The result for the multi-constituent substance (CAS RN 64742-95-6), a UVCB, characterizes the biodegradability of that substance

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

as a whole, but it does not suggest that each constituent is equally biodegradable. As with all ready biodegradation test guidelines, the test system and study design used with these substances (OECD TG 301F) is not capable of distinguishing the relative contribution of the substances' constituents to the total biodegradation measured.

- Based on Henry's Law constants (HLCs) representing a potential to volatilize from water that range from 590 to 1000 Pa-m³/mole, the potential to volatilize from surface waters for chemicals in the C9 Aromatic Hydrocarbon Solvents Category is expected to be high.
- Based on the measured bioconcentration factors that range from 23 to 342 for 1,2,4-trimethylbenzene and 1,3,5-trimethylbenzene, the category members are not expected to be bioaccumulative.
- Ecotoxicity
- Acute toxicity values used to characterize this category for fish (LL50; LC50) and invertebrates (EL50; EC50) range from 3.5 to 9.2 mg/L, based on measured data. For algae, one study for a category member (CAS RN 64742-95-6) resulted in a 72-hr EC50 of 2.4 mg/L (biomass) and 2.7 mg/L (growth rate) based on measured concentrations.
- The algal 72-hour NOEC (no observed effect concentration) for biomass and growth rate is 1.3 mg/L, based on mean measured concentrations. A 21-day Daphnia magna reproduction study with 1,3,5-trimethylbenzene (CAS RN 108-67-8) resulted in a NOEC value of 0.4 mg/L, based on a minimum measured value.
- Most ethers are very resistant to hydrolysis, and the rate of cleavage of the carbon-oxygen bond by abiotic processes is expected to be insignificant.
- Direct photolysis will not be an important removal process since aliphatic ethers do not absorb light at wavelengths >290 nm
- For Xylenes:
- log K_{oc} : 2.05-3.08; K_{oc} : 25.4-204; Half-life (hr) air : 0.24-42; Half-life (hr) H₂O surface water : 24-672; Half-life (hr) H₂O ground : 336-8640; Half-life (hr) soil : 52-672; Henry's Pa m³ /mol : 637-879; Henry's atm m³ /mol - 7.68E-03; BOD 5 if unstated - 1.4,1%; COD - 2.56,13% ThOD - 3.125 : BCF : 23; log BCF : 1.17-2.41.
- Environmental Fate: Most xylenes released to the environment will occur in the atmosphere and volatilisation is the dominant environmental fate process. Soil - Xylenes are expected to have moderate mobility in soil evaporating rapidly from soil surfaces. The extent of the degradation is expected to depend on its concentration, residence time in the soil, the nature of the soil, and whether resident microbial populations have been acclimated. Xylene can remain below the soil surface for several days and may travel through the soil profile and enter groundwater. Soil and water microbes may transform it into other, less harmful compounds, although this happens slowly. It is not clear how long xylene remains trapped deep underground in soil or groundwater, but it may be months or years.
- Atmospheric Fate: Xylene evaporates quickly into the air from surface soil and water and can remain in the air for several days until it is broken down by sunlight into other less harmful chemicals. In the ambient atmosphere, xylenes are expected to exist solely in the vapour phase. Xylenes are degraded in the atmosphere with an estimated atmospheric lifetime of about 0.5 to 2 days. Xylene may contribute to photochemical smog formation. p-Xylene has a moderately high photochemical reactivity under smog conditions, higher than the other xylene isomers. The photooxidation of p-xylene results in the production of carbon monoxide, formaldehyde, glyoxal, methylglyoxal, 3-methylbenzyl nitrate, m-tolualdehyde, 4-nitro-3-xylene, 5-nitro-3-xylene, 2,6-dimethyl-p-benzoquinone, 2,4-dimethylphenol, 6-nitro-2,4-dimethylphenol, 2,6-dimethylphenol, and 4-nitro-2,6-dimethylphenol.
- Aquatic Fate: p-xylene may adsorb to suspended solids and sediment in water and is expected to volatilise from water surfaces. Estimated volatilisation half-lives for a model river and model lake are 3 hours and 4 days, respectively. Measurements taken from goldfish, eels and clams indicate that bioconcentration in aquatic organisms is low. Photo-oxidation in the presence of humic acids may play an important role in the abiotic degradation of p-xylene. p-Xylene is biodegradable and has been observed to degrade in pond water however; it is unclear if it degrades in surface waters. p-Xylene has been observed to degrade in anaerobic and aerobic groundwater; however, it is known to persist for many years in groundwater, at least at sites where the concentration might have been quite high. Ecotoxicity: Xylenes are slightly toxic to fathead minnow, rainbow trout and bluegill and not acutely toxic to water fleas. For Photobacterium phosphoreum EC50 (24 h): 0.0084 mg/L. and Gammarus lacustris LC50 (48 h): 0.6 mg/L.
- **DO NOT discharge into sewer or waterways.**

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

PERSISTENCE AND DEGRADABILITY

Ingredient	Persistence: Water/Soil	Persistence: Air
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
dimethyl ether	LOW	LOW

BIOACCUMULATIVE POTENTIAL

Ingredient	Bioaccumulation
xylene	MEDIUM (BCF = 740)
ethanol	LOW (LogKOW = -0.31)
dimethyl ether	LOW (LogKOW = 0.1)

MOBILITY IN SOIL

Ingredient	Bioaccumulation
ethanol	HIGH (KOC = 1)
dimethyl ether	HIGH (KOC = 1.292)

SECTION 13 DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS

Product / Packaging disposal	<p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <p>Reduction Reuse Recycling Disposal (if all else fails)</p> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> • DO NOT allow wash water from cleaning or process equipment to enter drains. • It may be necessary to collect all wash water for treatment before disposal. • In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. • Where in doubt contact the responsible authority. • Consult State Land Waste Management Authority for disposal. • Discharge contents of damaged aerosol cans at an approved site. • Allow small quantities to evaporate. • DO NOT incinerate or puncture aerosol cans. • Bury residues and emptied aerosol cans at an approved site.
------------------------------	---



RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 14 TRANSPORT INFORMATION

LABELS REQUIRED

	
Marine Pollutant	
HAZCHEM	Not Applicable

LAND TRANSPORT (ADG)

UN number	1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	Class 2.1
	Subrisk Not Applicable
Packing group	Not Applicable
Environmental hazard	Environmentally hazardous
Special precautions for user	Special provisions 63 190 277 327 344 381
	Limited quantity 1000ml

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

AIR TRANSPORT (ICAO-IATA / DGR)

UN number	1950	
UN proper shipping name	Aerosols, flammable (engine starting fluid); Aerosols, flammable	
Transport hazard class(es)	ICAO/IATA Class	2.1
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	10L
Packing group	Not Applicable	
Environmental hazard	Environmentally hazardous	
Special precautions for user	Special provisions	A145 A167 A802; A1 A145 A167 A802
	Cargo Only Packing Instructions	203
	Cargo Only Maximum Qty / Pack	150kg
	Passenger and Cargo Packing Instructions	203; Forbidden
	Passenger and Cargo Maximum Qty / Pack	75kg; Forbidden
	Passenger and Cargo Limited Quantity Packing Instructions	Y203; Forbidden
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G; Forbidden

SEA TRANSPORT (IMDG-CODE / GGVSEE)

UN number	1950	
UN proper shipping name	AEROSOLS	
Transport hazard class(es)	IMDG Class	2.1
	IMDG Subrisk	Not Applicable
Packing group	Not Applicable	
Environmental hazard	Marine Pollutant	
Special precautions for user	EMS Number	F-D , S-U
	Special provisions	63 190 277 327 344 381 959
	Limited Quantities	1000ml

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 15 REGULATORY INFORMATION

SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS / LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

XYLENE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Inventory of Chemical Substances (AICS)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

FERRIC OXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT IS FOUND ON THE

FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Inventory of Chemical Substances (AICS)

ETHANOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

ZINC PHOSPHATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Inventory of Chemical Substances (AICS)

DIMETHYL ETHER IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Inventory of Chemical Substances (AICS)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
Chemical Footprint Project - Chemicals of High Concern List
Australia Inventory of Chemical Substances (AICS)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

National Inventory	Status
Australia - AIICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (xylene; ferric oxide; naphtha petroleum, light aromatic solvent; ethanol; dimethyl ether)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (zinc phosphate)
Vietnam - NCI	Yes
Russia - ARIPS	Yes

LEGEND

YES = ALL CAS DECLARED INGREDIENTS ARE ON THE INVENTORY

NO = ONE OR MORE OF THE CAS LISTED INGREDIENTS ARE NOT ON THE INVENTORY AND ARE NOT EXEMPT FROM LISTING (SEE SPECIFIC INGREDIENTS IN BRACKETS)

SILVER ZINC SUPPLIES | ABN: 58 997 237 445 | (07) 3287 4567

silverzinc.com.au | orders@silverzinc.com.au UNIT 2/10 MAIELLA ST, STAPYLTON, QLD 4207

SILVER
SZ INC
SUPPLIES

RED OXIDE PRIMER

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

CHEMWATCH:
VERSION NO:
ISSUE DATE:
PRINT DATE:

SECTION 16 OTHER INFORMATION

Revision Date	01/11/2019
Initial Date	28/04/2014

SDS VERSION SUMMARY

Version	Issue Date	Sections Updated
8.1.1.1	14/08/2016	Acute Health (skin), Classification
9.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

OTHER INFORMATION

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

DEFINITIONS AND ABBREVIATIONS

- PC - TWA: Permissible Concentration-Time Weighted Average
- PC - STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit
- IDLH: Immediately Dangerous to Life or Health Concentrations
- OSF: Odour Safety Factor
- NOAEL :No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700