TECHNICAL DATA SHEET

SPOT SURVEY SITE MARKER PAINT

SPOT SURVEY SITE MARKER PAINT



Spot Survey site marker paint is a premium marking out paint designed for a range of applications including; construction, landscaping, civil works and surveying. Spot Survey site marker paint is suitable for use with the Long Arm Handle and 2-Wheel spot Marking Handle, also available from Silver Zinc Supplies.

TECHNICAL DATA

Size	350g Aerosol
Colour	8 Standard and 8 Fluro Colours
Finish	
Consistency	
Propellant	1. Hydrocarbon / Dimethyl Ether 2. Post Nov 2020:Hydrocarbon

DIRECTION FOR USE

SUITABLE SURFACES:

Concrete, bitumen, steel and timber.

IDEAL APPLICATION TEMPERATURE:

Between -10°C and 30°C. Avoid use in windy conditions.

PREPARATION:

Shake can for at least 45 seconds AFTER the mixing ball begins to rattle. Shake can occasionally during use.

APPLICATION:

Hold can in the INVERTED position (upside down), approximately 10-15cm from the surface. Spray width can be adjusted by moving closer or further from the surface to be sprayed.

COVERAGE:

Will produce 200+ 'X' marks, up to 120 linear metres (depending on surface and colour used).

DRYING TIME:

Touch dry in 5 minutes (25°C). Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

AFTER SPRAYING:

Prevent blocking by holding the can UPRIGHT and spraying until only clear gas escapes. Also wipe spray tip of nozzle clean. Clean up wet paint with mineral turpentine, xylene or general purpose thinner.

CAUTION:

Painted surfaces may become slippery when wet. Refer to disclaimer.

STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Store in well-ventilated place.

DISPOSAL

Pressurised container: Do not pierce or burn, even after use. Aerosol should be completely emptied prior to disposal. Dispose of contents/container accoding to regional regulation.

FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website:

www.silverzinc.com.au

Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Silver Zinc Supplies; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Silver Zinc Supplies recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Sales and Customer Support Centre on 1300 2653 425.

