CYNOX LANOLIN SPRAY SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

SECTION 1 IDENTIFICATION

PRODUCT IDENTIFIER

| Product Name | Cynox Heavy Duty Lanolin Spray |
|---|---|
| Synonyms | Lanolin Spray |
| Recommended Use of the Chemical and Restriction on Use | Water resistant, water dispersed, anti corrosive, spray for use on all ferrous and non ferrous materials such as steel, iron, stainless steel, copper, timber, leather, vinyl, canvas, plastics, etc. |
| Manufacturer's product code(s) | OZS300C |

| UN number | 1950 |
|-----------------------|-------------------|
| Proper shipping name | AEROSOL FLAMMABLE |
| Dangerous Goods Class | 2.1 |
| Packing group | None Allocated |
| Subsidiary risk | None Allocated |
| Hazchem Code | 2Y |
| Poison Schedule | S 5 |

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

| Registered company name | Silver Zinc Supplies |
|-------------------------|---|
| Address | 2/10 Maiella Street Stapylton Queensland 4207 Australia |
| Telephone | (07) 3287 4567 |
| Website | silverzinc.com.au |
| Email | orders@silverzinc.com.au |

EMERGENCY CONTACT NUMBER

| Association / Organization | Silver Zinc Supplies |
|----------------------------|----------------------|
| Emergency Contact | 04000 18006 |
| Other Emergency Contact | Not Available |



SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

SECTION 2 HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA NOT A DANGEROUS GOODS ACCORDING TO THE CRITERIA OF THE ADG CODE

LABEL ELEMENTS





(Xn) Harmful

RISK PHRASES

| | R65 | Harmful: May cause lung damage if swallowed |
|--|-----|---|
|--|-----|---|

SAFETY PHRASES

| \$2 | Keep out of the reach of children |
|-----|---|
| S23 | Do not breathe vapor |
| S24 | Avoid contact with skin |
| S62 | If swallowed, do not induce vomiting: seek medical advice immediately and show container or label |

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS

| CAS No. | % [Proportion] | Name |
|------------|----------------|--|
| 8006-54-0 | 10-30 | Lanolin Anhydrous |
| 64742-81-0 | >60 | Proprietary blend hydrocarbon solvents |
| | 100 (Balance) | Ingredients determined to be non-hazardous |



SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

SECTION 4 FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

| Eye Contact | If material is splashed into eyes, immediately, flush with plenty of water for 15 minutes, ensuring eyelids are held open. If irritation persists transport to hospital or doctor. |
|----------------------|---|
| Skin Contact | If material is splashed onto the skin, remove any contaminated clothing and wash skin thoroughly with soap and water. If irritation persists transport to hospital or doctor. |
| Inhalation | Move victim to fresh air. Lay patient down. Keep warm and rested |
| Ingestion | If swallowed, DO NOT induce vomiting. Give water or milk to rinse out mouth then give liquid slowly and as much as can comfortably be drunk. Seek medical advice. |
| First Aid Facilities | Eye wash fountain, safety shower and normal washroom facilities. |
| Advice to Doctor | Treat symptomatically |

IN CASE OF POISONING, CONTACT POISONS INFORMATION CENTRE

IN AUSTRALIA CALL TEL; 131126

IN NEW ZEALAND TEL: 0800 POISON (0800 764 766)

SECTION 5 FIREFIGHTING MEASURES

| Fire / Explosion Hazard | If safe to do so, move undamaged containers from fire area. |
|----------------------------------|--|
| Hazardous Decomposition Products | May decompose on heating emitting oxides of carbon. May emit acrid smoke. |
| Fire Fighting Procedures | Fire fighters to wear Self-contained breathing apparatus (SCBA) in confined spaces, in oxygen deficient atmospheres or if exposed to products of decomposition. Full protective clothing is also recommended. |
| Extinguishing Media | Foam,Dry chemical,carbon dioxide,water fog. |
| Flammability | This material is a combustible liquid at elevated temperatures. Explosive air vapour mixture may form. Keep away from heat, naked flames, sparks. Electrically earth all equipment. |



SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

SECTION 6 ACCIDENTAL RELEASE MEASURES

| Minor Spills | Eliminate ignition sources. Shut off leak if safe to do so Material may be slippery when spilt. Walk cautiously. Collect and seal in properly labeled containers for disposal |
|--------------|---|
| Major Spills | Eliminate ignition sources. Shut off leak if safe to do so Wear chemical resistant gloves, overalls and safety glasses. Prevent by bunding or damming or by any other means, spillage from entering drains or watercourses. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect residues and seal in labeled drums for disposal. Wash spill area thoroughly with water and suitable detergent. |

SECTION 7 HANDLING AND STORAGE

COMBUSTIBLE FOR STORAGE. Store in a cool place and out of direct sunlight. Store away from sources of heat or ignition. Store away from oxidizing agents. Keep containers closed, when not using the product. Store in original packages as approved by manufacturer.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE STANDARDS No exposure standards have been assigned by the National Occupational Health & Safety Commission (NOHSC) for this product however the suggested exposure limit for the hydrocarbon content is (O.E.L.) 100 ppm. TWA.

| Engineering Controls | Maintain adequate ventilation at all times. In most circumstances natural ventilation systems are adequate unless the material is heated, reacted or otherwise changed in some type of chemical reaction, then the use of a local flameproof exhaust ventilation system is recommended. |
|-------------------------|--|
| Respiratory Protection | Avoid breathing of vapours/gases. Select and use respirators in accordance with AS/NZS 1715/1716. The use of a dust mask (disposable) or a half-face respirator with P1 filter is recommended. Filter capacity and respirator type depends on exposure levels and type of contaminant. If entering spaces where the airborne concentration of a contaminant is unknown then the use of a Self-contained breathing apparatus (SCBA) with positive pressure air supply complying with AS/NZS 1715 / 1716, or any other acceptable International Standard is recommended. |
| | GLOVES: Not normally required, however, if handling large quantities or if the skin is likely to be |
| Skin Protection | exposed to this product over prolonged periods, then the use of chemical resistant gloves is recommended. |
| Eye and Face Protection | Chemical goggles or face shield to protect eyes. |



SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

INFORMATION ON BASIC PHYSICAL AND CHIMICAL PROPERTIES

| Appearance | Aerosol |
|------------|---------------|
| Colour | Yellowish/tan |

SECTION 10 STABILITY AND REACTIVITY

| Stability | Stable under normal conditions of use. | |
|----------------------------------|---|--|
| Conditions to avoid | High temperatures and incompatibles. | |
| Incompatible materials | Oxidizing agents. | |
| Hazardous decomposition products | Emits smoke and fumes when heated to decomposition. | |
| Hazadous Polymerization | Will not occur | |

SECTION 11 TOXICOLOGICAL INFORMATION

THERE IS NO TOXICOLOGICAL INFORMATION AVAILABLE FOR THIS PRODUCT.

SECTION 12 ECOLOGICAL INFORMATION

100% BIODEGRADABLE DEGRADES RAPIDLY

SECTION 13 DISPOSAL CONSIDERATIONS

100% BIO REFER TO APPROPRIATE AUTHORITY IN YOUR STATE. DISPOSE OF MATERIAL THROUGH A LICENSED WASTE CONTRACTOR.

NORMALLY SUITABLE FOR DISPOSAL BY APPROVED WASTE DISPOSAL AGENT. DEGRADABLE DEGRADES RAPIDLY

SECTION 14 STRANSPORT INFORMATION

| UN number | 1950 | |
|-------------------------|----------------|--|
| UN proper shipping name | AEROSOLS | |
| Dangerous Goods Class | 2.1 | |
| Packing group | None Allocated | |
| Subsidiary risk | None Allocated | |
| Hazchem Code | 2Y | |
| Poison Schedule | S 5 | |



SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

SECTION 15 REGULATORY INFORMATION

(DUE TO SOLVENT CONTENT)

RISK PHRASES

| R65 | May cause lung damage if swallowed |
|-----|------------------------------------|
|-----|------------------------------------|

SAFETY PHRASES

| \$2 | Keep out of the reach of children | |
|-----------------|--|--|
| S16 | Keep away from sources of ignition – no smoking. | |
| S23 - S24 - S25 | Avoid contact with skin and eyes. | |
| \$36 | Wear suitable protective clothing. | |
| \$45 | In case of accident or if you feel unwell, contact a Doctor or Poisons Information Centre and show them this SDS | |

POISON CLASSIFICATION: S5

SECTION 16 OTHER INFORMATION

AQIS Approval No. IOA 5049 Commonwealth of Australia, Export Control Act 1982 High voltage testing by Energex:

| Dry Leakage | 70 KV / 300mm | 9.3 mA |
|-------------|---------------|--------|
| Wet Leakage | 70 KV / 300mm | 9.3 mA |

Disclaimer

The information herein is to the best of our knowledge, correct and complete. It describes the safety requirements for this product and should not be construed as guaranteeing specific properties. Since methods and conditions are beyond our control we do not accept liability for any damages resulting from the use of, or reliance on, this information in inappropriate contexts.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700

