

LINE MARKING PAINT



Line Marking Paint is a fast drying, acrylic based paint specially formulated to provide long lasting lines. Line Marking Paint is ideal for marking on; car parks, factories, warehouses, sporting fields and courts. Line Marking Paint is designed for use with a Line Making Machine. The Line Marking Machine features a built in side line attachment and removable Spot Marking Handle.

TECHNICAL DATA

Size	500g Aerosol
Colour	Yellow and White
Finish	Matt
Consistency	Liquid
Propellant	1.Hydrocarbon / Dimethyl ether 2.Post Nov 2020: Hycrocarbon

DIRECTION FOR USE

SUITABLE SURFACES:

Concrete, bitumen, steel and timber.

IDEAL APPLICATION TEMPERATURE:

Between -10°C and 30°C. Avoid use in windy conditions.

PREPARATION:

Shake can for at least 45 seconds AFTER the mixing ball begins to rattle. Shake can occasionally during use.

APPLICATION:

For INVERTED USE only. Insert can into the Line Marking machine's spot marking handle. Ensure the nozzle is correctly seated. To achieve the narrowest line width, the spot marking handle must be inserted into the lowest position. Line width can be increased by raising the handle in the slot. Line width can be adjusted approximately 60-100mm. Test line width on cardboard sheet until desired width is achieved. Masking wheels are designed to sharpen the lines by catching any over spray at the edges only. When marking grass/turf consider using specialized paint as it will minimize damage to the grass.

COVERAGE:

Will produce 80-100mm in a 50mm continuous line, or cover 4-6 m2. (depending on surface and colour used).

DRYING TIME:

Touch dry in 5 minutes (25°C). Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

AFTER SPRAYING:

Prevent blocking by holding the can UPRIGHT and spraying until only clear gas escapes. Also wipe spray tip of nozzle clean. Clean up wet paint with mineral turpentine, xylene or general purpose thinner.

CAUTION:

Painted surfaces may become slippery when wet. Refer to disclaimer.

STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Store in well-ventilated place.

DISPOSAL

Pressurised container: Do not pierce or burn, even after use. Aerosol should be completely emptied prior to disposal. Dispose of contents/container according to regional regulation.

FIRST AID / SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website:

www.silverzinc.com.au

Call a POISON CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician if you feel unwell. Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The performance of this product will depend on many factors outside the control of Silver Zinc Supplies; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Silver Zinc Supplies recommends customers undertake their own risk assessment prior to use, to determine the suitability of the product for the particular use intended.

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Sales and Customer Support Centre on 1300 2653 425.



ABN: 58 997 237 445