



SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: MP03, 750ml
 MP04, 5lt
 MP05, 20lt
Product Name: Mako Multipurpose
Revision Date: March 12, 2025
Version: 1.0
Manufacturer's Name: Touchwood International Pty Ltd
Address: Trading as Mako Technologies Australia Pty Ltd
 113 Alexander Drive, Mission Beach QLD 4852
Emergency Phone: 0417 240 429
DatePrinted: March 12, 2025
Supersedes Date: N.A.

Product/Recommended Uses: Penetrating lubricating oil, moisture and corrosion inhibitor

SECTION 2) HAZARDS IDENTIFICATION

Pictograms



Signal Word

Danger

SUSMP Classification

S5

Hazardous Statements - Health

Causes eye irritation
 Repeated exposure may cause skin dryness or cracking.
 Toxic if inhaled
 Harmful if swallowed
 May be fatal if swallowed and enters airways

Hazardous Statements - Physical

Combustible Liquid



MAKO NON-AEROSOLS 750ml, 5lt & 20lt^{2/8}

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

Precautionary Statements - Prevention

Wash hands, face and exposed skin thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not eat, drink or smoke when using this product.

Precautionary Statements - Response

Specific treatment- see First Aid on this label.

Use dry chemical, foam, carbon dioxide to extinguish.

IF SWALLOWED: Do NOT induce vomiting.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local, regional, national and international regulations.

SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0008016-13-5	FISH OIL	60% - 100%
0064742-48-9	NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	30% - 60%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.



MAKO NON-AEROSOLS 750ml, 5lt & 20lt ^{3/8}

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air, keep comfortable for breathing and keep warm. IF exposed or concerned: Get medical advice/attention. If unwell: Get medical advice/attention. Eliminate all ignition sources if safe to do so.

Eye Contact

Immediately call a POISON CENTER/doctor. Avoid direct contact. Wear chemical protective gloves, if necessary. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face.

Skin Contact

Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Immediately call a POISON CENTER/doctor. Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes. Wash contaminated clothing before re-use or discard. If skin irritation occurs: Get medical advice/attention.

Ingestion

Rinse mouth. IF exposed or concerned: Get medical advice/attention. Give a glass of water to drink. Do NOT induce vomiting. If vomiting occurs naturally, give further water. Call a POISON CENTER/doctor if you feel unwell. Never give anything by mouth to an unconscious or convulsing person.

Most Important Symptoms and Effects, Both acute and Delayed

Swelling, redness, blistering or irritation.

Indication of Any Immediate Medical Attention and Special Treatment Needed

Treat symptomatically.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small Fire: Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Large Fire: Water spray, fog or alcohol-resistant foam. Use caution when applying carbon dioxide in confined spaces.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards in Case of Fire

Containers may explode in fire. Vapors may travel to source of ignition and flash back. Non-combustible, substance itself does not burn but may decompose upon heating to produce corrosive fumes. Runoff to sewer may create fire or explosion hazard.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters. Damaged cylinders should be handled only by specialists.

Special Protective Actions

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.



MAKO NON-AEROSOLS 750ml, 5lt & 20lt^{4/8}

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Ventilate closed spaces before entering. Stay uphill and/or upstream. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Recommended Equipment

Wear chemical protective clothing.

Personal Precautions

Avoid breathing gas.

DO NOT breathe gas, vapor or mist.

DO NOT get on skin, eyes or clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and Materials for Containment and Cleaning up

Ventilate area after clean-up is complete. For large spills: absorb with vermiculite, dry sand, earth, or similar inert material and deposit in sealed containers for disposal. Use clean, non-sparking tools to collect absorbed material.

SECTION 7) HANDLING AND STORAGE

General

Remove contaminated clothing and protective equipment before entering eating areas.

Do not breathe vapors, mists or aerosols.

All containers must be properly labelled.

Eyewash stations and showers should be available in areas where this material is used and stored.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

Storage Room Requirements

Store gas cylinders separately, away from processing and handling areas, and from incompatible materials. Store, handle, and use corrosive materials in well-ventilated areas. Protect containers against banging or other physical damage when storing, transferring, or using them. Keep away from incompatible materials (e.g. oxidizers). Keep containers securely sealed when not in use, check regularly for leaks. Store at temperatures above their respective freezing/melting point, do not expose to temperatures exceeding 50 °C/122 °F. Empty containers retain residue and may be dangerous. Store in dry, well-ventilated, cool areas, out of direct sunlight and away from incompatible materials and other sources of heat.



MAKO NON-AEROSOLS 750ml, 5lt & 20lt^{5/8}

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

8

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear safety glasses with side shields.

Skin Protection

Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to AS/NZS 1715 and AS/NZS 1716 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH TWA (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	WES TWA (mg/m3)
NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	[(L)[N159](L)[N800]]; [5 (I)[N159]5 (I)[N800]];			(L)[N159](L)[N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	URT irr[N159]URT irr[N800]	[A2[N159]A2[N800]]; [A4[N159]A4[N800]];	

Chemical Name	WES STEL (ppm)	WES STEL (mg/m3)	WES TWA (ppm)	WES HEALTH OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)
NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)				500	2000		

Chemical Name	OSHA Skin designation	OSHA Carcinogen
NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)		

URT - Upper respiratory tract



MAKO NON-AEROSOLS 750ml, 5lt & 20lt^{6/8}

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	6.93 lb/gal
Specific Gravity	0.83
% VOC	96.38%
Density VOC	6.68 lb/gal
% Solids By Weight	0.00%
Appearance	Amber liquid
Odor Description	Characteristic odour
Odor Threshold	Data not available
pH	Data not available
Water Solubility	Insoluble
Flammability	Data not available
Flash Point Symbol	Data not available
Flash Point	Data not available
Viscosity	Data not available
Lower Explosion Level	Data not available
Vapor Pressure	Data not available
Upper Explosion Level	Data not available
Vapor Density	Data not available
Freezing Point	Data not available
Melting Point	Data not available
Low Boiling Point	Data not available
High Boiling Point	Data not available
Auto Ignition Temp	Data not available
Decomposition Pt	Data not available
Evaporation Rate	Data not available
Coefficient Water/Oil	Data not available

SECTION 10) STABILITY AND REACTIVITY

Stability

The product is stable under normal storage conditions.

Conditions to Avoid

Avoid heat, sparks, flame, elevated temperatures, sources of ignition and contact with incompatible materials. Elevated temperatures and sources of ignition.

Hazardous Reactions/Polymerization

Will not occur.

Incompatible materials

Oxidizing agents.

Hazardous Decomposition Products

Oxides of carbon and nitrogen, smoke and other toxic fumes.



MAKO NON-AEROSOLS 750ml, 5lt & 20lt^{7/8}

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

No data available.

Carcinogenicity

No data available.

Serious Eye Damage/Irritation

Causes eye irritation

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

Vapor is a mild eye irritant.

Respiratory/Skin Sensitization

No data available.

Germ Cell Mutagenicity

No data available.

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

No data available.

Specific Target Organ Toxicity - Repeated Exposure

No data available.

Aspiration Hazard

May be fatal if swallowed and enters airways

Acute Toxicity

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

Inhalation of high concentrations can cause CNS depression; Ingestion can cause aspiration into the lungs.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

No data available.

Persistence and Degradability

No data available.

Bio-accumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0064742-48-9 NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)

The substance is not PBT / vPvB.



MAKO NON-AEROSOLS 750ml, 5lt & 20lt^{8/8}

SAFETY DATA SHEET ACCORDING TO WHS AND ADG REQUIREMENTS

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14) TRANSPORT INFORMATION

ADG Information

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

IMDG Information

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

IATA Information

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

SECTION 15) REGULATORY INFORMATION

- All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

HSNO Group Standard: Aerosols Flammable Group Standard 2006: HSR002515

CAS	Chemical Name	% By Weight	Regulation List
0008016-13-5	FISH OIL	60% - 100%	DSL,VOC,TSCA
0064742-48-9	NAPHTHA, HEAVY HYDROTREATED (PETROLEUM)	30% - 60%	DSL,VOC,IARC Carcinogen,TSCA

SECTION 16) OTHER INFORMATION INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS

Glossary

ACGIH- American Conference of Governmental Industrial Hygienists; ADG- Australian Dangerous Goods Code; CAS- Chemical Abstract Service; DSL- Domestic Substances List; LC- Lethal Concentration; LD- Lethal Dose; OSHA- Occupational Safety and Health Administration; SCBA- Self Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; VOC- Volatile Organic Compounds; WES- Workplace Exposure Standards

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

MP03, 750ml
MP04, 5lt
MP05, 20lt

www.mmpindustrial.com.au